

Yield Reporting Form

HP LaserJet Pro M203 Introductory cartridge model CF230A

Declared ISO yield

Toner cartridge yield

Average cartridge yield **1000** standard pages¹

Declared yield value in accordance with ISO/IEC 19752 based on continuous printing

Calculated test values

Average ¹	1,087
Standard Dev.	69
90% lower confidence limit ¹	1,063

Test date: beginning	2016/9/20
Test dates: ending	2016/9/29
Number of cartridges used in testing	24
Number of cartridges used in calculations	24
Type of cartridge	HP Introductory CF230A
Shake procedure used?	No
Print mode	Continuous
Job size	100 pages per job
Number of engines used in testing	4
Media	Double A 80g
Paper size	A4
Paper feed orientation	Short edge
Computer model	HP Compaq 6005 Pro
Operating system	Microsoft Windows 7 Enterprise with SP1
Application software	Adobe Reader 9
Print driver version	PCLmS
Connection type	network
Test page version*	Version 4.0 pdf
Power on/off every day	No

Engine serial numbers:

Engine Firmware Version:

VNC3J00016	20160526
VNC3J00024	20160526
VNC3J00015	20160526
VNC3J00021	20160526

*filename: Download_Free___19752_Test_Chart___pdf from ISO SC28 website

Cartridge testing data

Test environmental limits:	Temperature	Humidity
	°C	%RH
Max running average	24.0	46
Min running average	22.9	43
Average	23.5	44

CF230A		Laser Jet Pro M203dw	
Cartridge	Lot Code	Engine SerNo	Cartridge Yield
CF230A_Starter_1	6H05T1Ba	VNC3J00016	1144
CF230A_Starter_2	6H05T1Ba	VNC3J00024	1050
CF230A_Starter_3	6H05T1Ba	VNC3J00015	1077
CF230A_Starter_4	6H05T1Ba	VNC3J00021	1161
CF230A_Starter_5	6H22T1Aa	VNC3J00016	1084
CF230A_Starter_6	6H22T1Aa	VNC3J00024	1039
CF230A_Starter_7	6H22T1Aa	VNC3J00015	1027
CF230A_Starter_8	6H22T1Aa	VNC3J00021	1046
CF230A_Starter_9	6H25T2Aa	VNC3J00016	1152
CF230A_Starter_10	6H25T2Aa	VNC3J00024	1038
CF230A_Starter_11	6H25T2Aa	VNC3J00015	1010
CF230A_Starter_12	6H25T2Aa	VNC3J00021	1239
CF230A_Starter_13	6H05T1Ba	VNC3J00016	1193
CF230A_Starter_14	6H05T1Ba	VNC3J00024	1052
CF230A_Starter_15	6H05T1Ba	VNC3J00015	1060
CF230A_Starter_16	6H05T1Ba	VNC3J00021	1190
CF230A_Starter_17	6H22T1Aa	VNC3J00016	977
CF230A_Starter_18	6H15T1Aa	VNC3J00024	1075
CF230A_Starter_19	6H22T1Aa	VNC3J00015	1071
CF230A_Starter_20	6H15T1Aa	VNC3J00021	1058
CF230A_Starter_21	6H25T2Aa	VNC3J00016	1156
CF230A_Starter_22	6H25T2Aa	VNC3J00024	978
CF230A_Starter_23	6H25T2Aa	VNC3J00015	1090
CF230A_Starter_24	6H25T2Aa	VNC3J00021	1127

¹ In an ISO report two values are commonly listed: declared ISO yield and calculated test values. Generally, the calculated test values are higher than the declared ISO yield. Actual cartridge yields vary considerably based on content of images printed and other factors. For more information visit www.hp.com/go/learnaboutsupsies.