

ISO/IEC 24734 Printing Productivity Report: Office Category

Full Detailed Test Report - LETTER

Color LaserJet MFP M476DW

Printing device and settings	
Test Start Date and Time	7/29/2014 12:43
Tester	AH
Machine name/model	Color LaserJet MFP M476DW
Colour or B&W	Colour
FW Version	20140128
Temperature and Humidity	74 degF / 23 degC, 48 %RH
Voltage	110V
Test End Date and Time	8/4/2014 12:17

Item	Value	
Mode and Setting	Driver Version	61.155.1.16769
	Media/Quality Setting	Default / Default
	Simplex B&W Settings	Print in Grayscale
	Duplex B&W Settings	Print in Grayscale
	Setting N set count	Application
Collating function	Activated (application)	
Paper Path	Paper Sending Direction	Default
	Paper Size Setting	Default
	Paper Feeding	Tray 2
	Paper Exit	Standard Exit Tray
	Output Orientation	Default (face down)
	Duplexing Unit (Yes/No)	Yes
Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Colorlok / Xerox Business 4200

Summary Report: Letter			
Office Category Test for Color Device		FSOT (seconds)	ESAT (ipm)
Color	Simplex	25.0	21.1
	Duplex	38.1	10.5
B&W	Simplex	25.0	21.1
	Duplex	37.6	10.5

Notes
Measured using ISO/IEC 24734, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Detailed Report: LETTER						
	Office Category Test	FSOT (secs)	EFTP (ipm)		ESAT (ipm)	
		1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	1 set + 4min (# of sets)	1 set + 30sec
Color Mode	Simplex - Adobe Reader	25.30	9.48 (1 set)	16.22 (4 sets)	20.12 (24 sets)	21.15
	Simplex - Word	24.78	9.68 (1 set)	16.37 (4 sets)		21.16
	Simplex - Excel	24.75	9.69 (1 set)	16.37 (4 sets)		21.15
	Simplex - Average	25.0	9.6	16.3	20.1	21.1
	Duplex - Adobe Reader	38.61	6.20 (1 set)	8.58 (3 sets)		10.58
	Duplex - Word	37.70	6.36 (1 set)	8.68 (3 sets)		10.58
	Duplex - Excel	37.94	6.30 (1 set)	8.66 (3 sets)		10.58
	Duplex - Average	38.1	6.2	8.6		10.5
B&W mode (optional for color device)	Simplex - Adobe Reader	25.28	9.49 (1 set)	16.23 (4 sets)	18.25 (24 sets)	21.13
	Simplex - Word	24.69	9.71 (1 set)	16.39 (4 sets)		21.15
	Simplex - Excel	24.75	9.69 (1 set)	16.37 (4 sets)		21.15
	Simplex - Average	25.0	9.6	16.3	18.2	21.1
	Duplex - Adobe Reader	37.89	6.32 (1 set)	8.68 (3 sets)		10.58
	Duplex - Word	37.22	6.44 (1 set)	8.74 (3 sets)		10.58
	Duplex - Excel	37.42	6.40 (1 set)	8.72 (3 sets)		10.58
	Duplex - Average	37.6	6.3	8.7		10.5

Notes
Measured using ISO/IEC 24734, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Test System Parameters	
Item	Value
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 - 3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aCSHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
TCP/IP	TCP/IP 10/1000
Operating System	Windows 7 64 Bit
Printing Applications	Microsoft Office 2010
Microsoft Office	Office 2010
Adobe Reader	10
Test files and location	Office category files, hard drive

ISO/IEC 24734 Printing Productivity Report: Office Category

Full Detailed Test Report - A4

Color LaserJet MFP M476DW

Printing device and settings	
Test Start Date and Time	7/29/2014 12:43
Tester	AH
Machine name/model	Color LaserJet MFP M476DW
Colour or B&W	Colour
FW Version	20140128
Temperature and Humidity	74 degF / 23 degC, 48 %RH
Voltage	110V
Test End Date and Time	8/4/2014 12:17

Item	Value	
Mode and Setting	Driver Version	61.155.1.16769
	Media/Quality Setting	Default / Default
	Simplex B&W Settings	Print in Grayscale
	Duplex B&W Settings	Print in Grayscale
	Setting N set count	Application
	Collating function	Activated (application)
Paper Path	Paper Sending Direction	Default
	Paper Size Setting	Default
	Paper Feeding	Tray 2
	Paper Exit	Standard Exit Tray
	Output Orientation	Default (face down)
	Duplexing Unit (Yes/No)	Yes
Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Colorlok / Xerox Business 4200

Summary Report: A4			
Office Category Test for Color Device		FSOT (seconds)	ESAT (ipm)
Colour	Simplex	25.7	20.0
	Duplex	38.7	10.3
B&W	Simplex	25.6	20.0
	Duplex	38.1	10.3

Notes
Measured using ISO/IEC 24734, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Detailed Report: A4						
	Office Category Test	FSOT (secs)	EFTP (ipm)			ESAT (ipm)
			1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	
Colour Mode	Simplex - Adobe Reader	26.02	9.22 (1 set)	15.57 (4 sets)	18.11 (23 sets)	20.07
	Simplex - Word	25.43	9.43 (1 set)	15.71 (4 sets)		20.07
	Simplex - Excel	25.36	9.44 (1 set)	15.72 (4 sets)		20.07
	Simplex - Average	25.7	9.3	15.6	18.1	20.0
	Duplex - Adobe Reader	39.11	6.12 (1 set)	8.40 (3 sets)		10.30
	Duplex - Word	38.30	6.26 (1 set)	8.50 (3 sets)		10.30
	Duplex - Excel	38.40	6.24 (1 set)	8.48 (3 sets)		10.30
	Duplex - Average	38.7	6.2	8.4		10.3
B&W mode (optional for color device)	Simplex - Adobe Reader	25.89	9.26 (1 set)	15.61 (4 sets)	17.62 (23 sets)	20.07
	Simplex - Word	25.35	9.46 (1 set)	15.73 (4 sets)		20.05
	Simplex - Excel	25.37	9.44 (1 set)	15.72 (4 sets)		20.07
	Simplex - Average	25.6	9.3	15.6	17.6	20.0
	Duplex - Adobe Reader	38.40	6.24 (1 set)	8.48 (3 sets)		10.30
	Duplex - Word	37.85	6.32 (1 set)	8.52 (3 sets)		10.30
	Duplex - Excel	37.97	6.30 (1 set)	8.52 (3 sets)		10.30
	Duplex - Average	38.1	6.2	8.5		10.3

Notes
Measured using ISO/IEC 24734, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Test System Parameters	
Item	Value
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 - 3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aCXHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
TCP/IP	TCP/IP 10/1000
Operating System	Windows 7 64 Bit
Printing Applications	Microsoft Office 2010
Microsoft Office	Office 2010
Adobe Reader	10
Test files and location	Office category files, hard drive

ISO/IEC 29183 Copy Productivity Report

Full Detailed Test Report - LETTER

Color LaserJet MFP M476DW

Machine Setup Information	
Test Start Date and Time	7/29/2014 12:43
Tester	AH
Machine name/model	Color LaserJet MFP M476DW
Colour or B&W	Colour
Configuration (options)	Not Specified
Temperature and Humidity	74 degF / 23 degC, 48 %rH
Test End Date and Time	8/4/2014 12:17

	Pre-set Item	Pre-set Value
Mode	Output Resolution	Default
	Output Quality	Default
	Copying Mode	Colour for Colour and B&W for B&W
	Auto Density Adjustment	Default
	Collating function	Set in Control Panel
Paper	Paper Sending Direction	Default
	Paper Type Setting	Default
Paper Path	Paper Feeding	Tray 2
	Paper Exit	Default
	Face Up Exit	Default (face down)
Temporary Stop	Fixing Capability	Default
	Image Quality Stability	Default
	Capacity of Paper	Default
	Others	None

Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Colorlok / Xerox Business 4200

Summary Report: Letter		
	sFCOT	sESAT (ipm)
Color	20.8	21.1
B&W	15.1	21.1

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.

Detailed Report: LETTER						
	Target	sFCOT (secs)	sEFTP (ipm)			sESAT (ipm)
			1copy	1copy+30sec	1copy+4minutes	
Color	A	20.71	2.89	13.87 12 sets	17.87 87 sets	21.16
	B	20.71	2.89	13.86 12 sets		21.14
	C	20.72	2.89	14.24 13 sets		21.15
	D	20.73	2.89	14.24 13 sets		21.15
	Average	20.8	2.8	14.0	17.8	21.1
	B&W	A	15.05	3.98	15.57 12 sets	18.34 86 sets
B		15.04	3.98	15.89 13 sets		21.15
C		15.04	3.98	15.88 13 sets		21.15
D		15.07	3.98	15.89 13 sets		21.15
Average		15.1	3.9	15.8	18.3	21.1

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.

ISO/IEC 29183 Copy Productivity Report

Full Detailed Test Report - A4

Color LaserJet MFP M476DW

Machine Setup Information	
Test Start Date and Time	7/29/2014 12:43
Tester	AH
Machine name/model	Color LaserJet MFP M476DW
Colour or B&W	Colour
Configuration (options)	Not Specified
Temperature and Humidity	74 degF / 23 degC, 48 %rH
Test End Date and Time	8/4/2014 12:17

	Pre-set Item	Pre-set Value
Mode	Output Resolution	Default
	Output Quality	Default
	Copying Mode	Colour for Colour and B&W for B&W
	Auto Density Adjustment	Default
	Collating function	Set in Control Panel
Paper	Paper Sending Direction	Default
	Paper Type Setting	Default
Paper Path	Paper Feeding	Tray 2
	Paper Exit	Default
	Face Up Exit	Default (face down)
Temporary Stop	Fixing Capability	Default
	Image Quality Stability	Default
	Capacity of Paper	Default
	Others	None

Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m ²
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Colorlok / Xerox Business 4200

Summary Report: A4		
	sFCOT	sESAT (ipm)
Colour	20.9	20.1
B&W	15.2	20.0

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.

Detailed Report: A4						
	Target	sFCOT (secs)	sEFTP (ipm)			sESAT (ipm)
			1copy	1copy+30sec	1copy+4minutes	
Colour	A	20.88	2.87	13.40 12 sets	16.98 86 sets	20.07
	B	20.90	2.86	13.54 12 sets		20.46
	C	20.88	2.87	13.40 12 sets		20.07
	D	20.88	2.87	13.39 12 sets		20.07
	Average	20.9	2.8	13.4	16.9	20.1
	B&W	A	15.17	3.95	14.99 12 sets	19.18 86 sets
B		15.18	3.94	14.98 12 sets		20.07
C		15.21	3.94	14.97 12 sets		20.05
D		15.23	3.93	14.97 12 sets		20.07
Average		15.2	3.9	14.9	19.1	20.0

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.